

Our dedicated force of skilled craftsmen take pride in producing superior packaging machines.



Model S-23C High Production L-Sealer

- > **Semi-Automatic Operation**
- > **Sealer Size – 12 1/2"W x 17"L**
(19"L available)
- > **Speed – 20 to 30 packages per minute**
- > **Floor Space – 4' x 4' approximately**

The Model S-23C is a compact, productive machine with speeds approaching those of fully automatic L-Sealers. Centerfolded film is dispensed from a power unwind, over and through the film inverting head which turns the film inside out and leaves an opening for product insertion. Operation is simple... with one smooth motion, the operator inserts the product into the film and onto the seal area and then presses the "SEAL" buttons. Film unwind, sealing, discharge conveyor, and hole punch are all automatic. The Model S-23C is ideal for applications that require straight-line product flow and high production at a lower cost than fully automatic equipment. A package ejector can be installed in place of the discharge conveyor.



Model S-3CDA, USDA Approved, High Production L-Sealer

- > **Semi-Automatic Operation**
- > **Sealer Size – 12 1/2" W x 17" L**
(17"W and 19"L available)
- > **Speed – 20 to 30 packages per minute**
- > **Floor Space – 4' x 4' approximately**

The Model S-3CDA was designed specifically to meet the exacting requirements of food processing plants and is USDA approved for that use. The basic construction is stainless steel for easy wipe-down cleaning. Electrical components are shielded to protect them from overspray when steam cleaning the processing area.

Centerfolded film is dispensed from a power unwind and passes over and through a film inverting head which turns the film inside out, leaving an opening for product insertion. With one smooth motion, the operator inserts the product into the film and onto the sealing area, and then presses the "SEAL" buttons. Film unwind, sealing head, sealing cycle and product discharge are fully automatic.

